

# Product information

## Automatic Transmission Cleaner

PI 26/24/08/2021



### Description

Highly effective cleaning fluid for dissolving deposits and residues in automatic transmissions. Ensures optimal shifting performance and prolongs transmission service life. These highly effective detergent and dispersant additives in association with the carrier fluid have been successfully tested in the laboratory and in practical field trials for their ability to dissolve sludge and lacquer formers.

### Properties

- no pollution to the environment
- simple to use
- does not attack common sealing materials
- assures optimum shifting performance
- rapid cleaning
- gentle cleaning
- highly economical

### Technical data

Base	Additiv, Naphthenbasisches Spezialöl / additive, naphtha-base special oil
Viscosity index	204
Viscosity at 40 °C	58,0 mm <sup>2</sup> /s
Viscosity at 100 °C	11,8 mm <sup>2</sup> /s
Form	flüssig, liquid
Odor	charakteristisch / characteristic
Density at 15 °C	0,885 g/ml

### Areas of application

Suitable for all automatic transmissions.

### Application

Before changing the automatic transmission fluid, add the contents of the can to the gear oil when it is at operating temperature through the dipstick opening using a funnel. Allow the engine to run in neutral for approx. 10 minutes and shift through all gears at least twice with the vehicle in a stationary position. Change the oil and filters after cleaning with the appropriate LIQUI MOLY gear oil. The contents of one 300 ml can are sufficient to treat 6-9 liters of oil. Can also be used in all commercial automatic transmission cleaning devices. Always observe the work instructions of the equipment manufacturer!

### Available pack sizes

300 ml Can sheet metal	2512 D-GB-I-E-P
300 ml Can sheet metal	21515 F-D

**Our information is based on thorough research and may be considered reliable, although not legally binding.**